

# Rittal – The System.

Faster – better – everywhere.



undefined 9980.096

## WMV Vented Enclosures, Type 3R

State: 2023-10-20 (Source: [rittal.com/ca-en](https://www.rittal.com/ca-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# undefined 9980.096 - WMV Vented Enclosures, Type 3R

The WMV vented enclosure is a single door enclosure with roof module and door hood. The configuration includes pre-drilled mounting holes and integrated cooling with fans and filters.



## Features

Model No.	9980.096
Supply includes	Housing with vented roof module Door with fitted seal and vented hood Mounting plate Top-mounted 115V fans Thermostat Washable Filter kits
Dimensions	Width: 609 mm Height: 1,009 mm Depth: 304 mm
Dimensions of mounting plate (W x H)	549 mm x 870 mm
Lock	Lock version: 2 x quarter turn with HD lock inserts for 36" high and below No. of locks: 2
Type rating according to UL 50E	UL Type 3R UL Type 1 UL Type 12
Protection category NEMA	NEMA 3R NEMA 1 NEMA 12
Material thickness - door	2 mm

# Features

---

Material thickness - enclosure	1.5 mm
Material thickness – mounting plate	2.5 mm
Rated current	0.46 A
Air throughput (unimpeded air flow)	150 cfm
Fan size	4 in
UPC-Code	92347

# Approvals

---

Approvals	UL + C-UL (listed)
-----------	--------------------